

CODE TANK TRAILERS



SPECIFICATIONS:

Type:	Code Tank Trailer; ASME U, DOT 407/412
Capacity:	150 BBL, 6300 Gallons Plus/Minus 2%
Commodity:	Unspecified Oilfield Fluids
Design Pressure:	35 PSI Internal, 15 INHG External, 54 PSIG Hydrostatic Test
Shell:	1/4 PL x 59" O.D.
Head:	5/16" PL Code ASME Shape
Baffle:	Two 1/4" Dished
Stiffeners:	3/8" x 3" Rolled Rings (8) External
Suspension:	Hutch CH 9700 with 3-leaf High Arch Springs
Axles:	25,000# Round with Outboard Drums
Wheels:	10 Hole Steel Disc Hub Piloted
Tires:	11- 24.5 Radials, 16-Ply Anti-Chip, Cut Resistant
Brakes:	16-1/2" x 7" with Spring Parking, Auto Slacks, ABS One Axle
King Pin Plate:	3/8" Reinforced Plate, Bolt On Adjustable
Landing Gear:	Jost 50-K, 2 Speed, Heavy Duty, High Capacity Lift
Bumper:	1/4" x 4" x 6" Tube with Tow Eye
Fenders:	Full Length Formed Hose Pan with 1/4" Formed Supports
Tool Box:	18" x 18" x 36" Aluminum on Driver's Side with Sealed Door
Mud Flaps:	Galyean Anti Sail
Outlet:	Two 4" Butterfly Valves at Rear with a Wedge Sump
Vents:	1-1/2" Vacuum Relief, 2" Pressure Relief, both Located at Top Front Barrel, 2" Blow Down Line at Rear +30/-30 Pressure Gauge
Manways:	Three Located on Top, One on Rear Head, All 20" Domed Style with Plated Swing Bolts and Wing Nuts
Shut Off:	Primary in Front Manway; 10 Gallon Secondary with Drain
Lights:	Full DOT Sealed Lights, Harness and Junction Box with Terminal Strip, Two Rear Work Lights with Integral Switches, LED Lights
Sight Glass:	1-1/2" Plastic Sight Glass Tube Installed in Rear Head with Clean Out Tees and Isolation Ball Valves Top and Bottom, 3/4" Drain
Coating:	All Surfaces Grit blasted Near White, Interior Lined, Enviroline 375 15 Dry Mils, Exterior Coated with a High Build Corrosion Inhibitive Epoxy and Color Coated with a High Solids Acrylic Polyurethane Finish
Additional:	DOT Overturn protection – Tombstone Type, 4 Placards, Ladder at Center Driver's Side to Walkway with Handrails, OSHA Approved Safety Swing Gate
Additional Options:	Air Ride and Plumbing Options Available Upon Request

WE CUSTOMIZE TO MEET YOUR SPECIFICATIONS