

# 65 BBL VACUUM BOBTAIL TANK



## SPECIFICATIONS:

<b>Type:</b>	Vacuum Bobtail Tank; Non-Code
<b>Capacity:</b>	65 BBL, 2695 Gallons Plus 2%
<b>Commodity:</b>	Unspecified Oilfield Fluids
<b>Design Pressure:</b>	15 PSI Internal, 22 INHG External, 23 PSIG Hydrostatic Test
<b>Shell:</b>	1/4 PL x 72" O.D., 12' Length
<b>Head:</b>	1/4 PL Non Code ASME Shape
<b>Baffle:</b>	One 1/4" Dished
<b>Stiffeners:</b>	3/8" x 2-1/2" Rolled Rings (2) External
<b>Bumpers:</b>	1/4" x 6" x 4" Tube with Tow Eye
<b>Fenders:</b>	Full Length Formed Hose Pan with 1/4" Formed Supports
<b>Tool Box:</b>	Two 18 x 18 x 24 Aluminum
<b>Mud Flaps:</b>	Galyean Anti Sail
<b>Outlet:</b>	One 4" Butterfly Valve at Rear with a Wedge Sump
<b>Vents:</b>	1-1/2" Vacuum Relief, 2" Pressure Relief, both Located at Top Front Barrel, 2" Blow Down Line at Rear, +30/-30 Pressure Gauge
<b>Manways:</b>	Two Located on Top, One on Rear Head, All 20" Domed Style with Plated Swing Bolts and Wing Nuts, Gasket in Lid.
<b>Shut Off:</b>	Primary in Front Manway; 10 Gallon Secondary with Drain. Both equipped with 6" S/S Float Ball and 8" S/S Cage Assembly.
<b>Lights:</b>	Full DOT Sealed Lights, Harness and Junction Box with Terminal Strip, Two Rear Work Lights with Integral Switches, LED Lights.
<b>Sight Glass:</b>	1-1/2" Plastic Sight Glass Tube Installed in Rear Head with Clean Out Tees and Isolation Ball Valves Top and Bottom, 3/4" Drain.
<b>Coating:</b>	All Surfaces Grit blasted Near White, Interior Lined with Enviroline 375 @ 15 Dry Mills, Exterior Coated with a High Build Corrosion Inhibitive Epoxy @ 4-6 Dry Mills and Color Coated with a High Solids Acrylic Polyurethane Finish @ 2-4 Dry Mills.
<b>Catwalk:</b>	12" Wide Walkway with 1" Pipe Handrails Running Full Length with rear entry. Mounted at 9 o'clock on Driver's Side

**WE CUSTOMIZE TO MEET YOUR SPECIFICATIONS**