



GALYEAN



1225 Industrial Drive ♦ PO Box 1686 ♦ Henderson ♦ TX 75653

Phone: 903/657-7561 ♦ Fax: 903/657-0502

Web address: www.galyeantrailers.com ♦ e-mail: allen@galyean.com

Specification for Aluminum Vacuum Trailer:

- ♦ 6300 Gallon Single Compartment Vacuum Trailer
- ♦ 1/4" Aluminum Shell (length of shell 38')
- ♦ 64" O.D. x 1/4" F&D Heads and Bulkheads
- ♦ Ridewell Heavy Duty Air-Ride Suspension
- ♦ 2-25K PDC Axles with Spring Brakes and Outboard Drums
- ♦ 16-1/2" x 7" x 3/4" and Sealco 4S/2M ABS Air System
- ♦ 11R24.5 General Chip/Cut Resistant Tires on 10 Hole Steel Wheels
- ♦ 2-Speed Jost Roll-up 50K Rated Landing Gear
- ♦ Truck-Lite Light System with Two Work Lights on Rear Head
- ♦ DOT Overturn Protection - Tombstone Type
- ♦ 1- 18"x18"x36" Lockable Aluminum Diamond Plate Tool Box
- ♦ Front Poly-Minimizer Fenders and 20' Rear Hose Tray with Drains
- ♦ Ladder at Center Driver's Side to Full Length Catwalk with Handrails
- ♦ Grit Blast, Epoxy Base Coat Internal Liner Enviroliner 275, 15 dry mills

